



Typ ATMOS	DC 15 E	DC 18 S	DC 22 S	DC 25 S	DC 32 S	DC 40 SX	DC 50 S	DC 70 S	DC 20 GS	DC 25 GS	DC 32 GS	DC 40 GS	DC 50 GSX	DC 70 GSX	DC 75 SE	DC 100
Rozsah výkonu (kW)	10-14,9	14-20	15-22	17-25/27	24-35	28-40	35-49,9	49-70	14-20	17-25	24-32	28-40	35-49	70	75	99
Předep. tah komína (Pa)	18	20	23	23	24	24	25	30	20	23	25	25	25	30	30	35
Hmotnost kotle (kg)	280	265	324	326	366	368	433	515	343	431	436	485	538	571	700	820
Objem vody (l)	45	45	58	58	80	80	89	93	64	80	80	90	120	132	190	294
Obsah násypky (dm <sup>3</sup> )	66	66	100	100	140	140	180	180	87	125	125	170	210	210	345	400
Max. délka dřeva (mm)	330	330	530	530	530	530	730	730	330	530	530	530	530	530	1000	730
Spotř. na top. sez. Ø (prost. metry)	15	20	22	25	35	40	50	70	19	25	32	40	50	70	75	99
Předepsané palivo	<b>Suché dřevo</b> o výhřevnosti 15-18 MJ/kg, průměr 80-150 mm a vlhkosti 12-20%															průměr 100-200 mm
Minimální teplota vratné vody	65 °C															
Účinnost (%)	81 - 90 %														83%	89%
Třída kotle dle ČSN EN 303-5	3	4	4	4	4	4	4	3	4	4	4	4	5	4	3	3
Dotované kotle v ČR		•	•	•	•	•	•		•	•	•	•	•			